Date Issued: 9/30/2009 MSDS No: Q-Plus **Date Revised:** 10/14/2013

Revision No: 10

Q-Plus Solder Paste Flux

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Q-Plus Solder Paste Flux

PRODUCT DESCRIPTION: Q-Plus Soldering Paste Flux

MANUFACTURER

24 HR. EMERGENCY TELEPHONE NUMBERS

1-800-535-5053 Infotrac

1-352-323-3500 Outside the U.S.

Qualitek International, Inc.

315 Fairbank St. Addison, IL 60101

Emergency Phone: (800) 535-5053 **Service Number:** (630) 628-8083

2. HAZARDS IDENTIFICATION

GHS CLASSIFICATIONS

Environmental:

Acute Hazards to the Aquatic Environment, Category 1B

GHS LABEL







Corrosion Environment Exclamation mark

SIGNAL WORD: DANGER HAZARD STATEMENTS

H314: Causes severe skin burns and eye damage.

H413: May cause long lasting harmful effects to aquatic life.

POTENTIAL HEALTH EFFECTS

EYES: Causes eye burns.

SKIN: May cause skin irritation and burns.

INGESTION: May cause irritation of the mouth, throat, and gastrointestinal tract.

INHALATION: May be irritating to the mucous membranes and to the respiratory tract.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Date Issued: 9/30/2009 MSDS No: Q-Plus Date Revised: 10/14/2013

Revision No: 10

Q-Plus Solder Paste Flux

Chemical Name	Wt.%	CAS
Petrolatum USP	< 70	8009-03-8
Zinc chloride	< 25	7646-85-7
Ammonium chloride	< 5	12125-02-9

COMMENTS: SVHC - This product does not contain any substances of very high concern.

4. FIRST AID MEASURES

EYES: Remove any contact lenses. Immediately flush eyes with large quantities of water for at least 15 minutes. Do not attempt to neutralize with chemical agents. Get medical attention if irritation or vision problems develop.

SKIN: In case of contact, immediately wash with plenty of soap and water for at least 5 minutes. Seek medical attention if irritation developes or persists. Remove contaminated clothing and shoes. Clean contaminted clothing and shoes before re-use.

INGESTION: If victim is conscious, give several glasses of water and keep the airway clean. Get medical attention.

INHALATION: If symptoms of overexposure are experienced, evacuate to fresh air. If symptoms persist, seek medical attention.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

CHRONIC EFFECTS: Prolonged or repeated exposure due to ingestion may cause anemia, insomnia, weakness, constipation and abdominal pain. Prolonged or repeated exposure due to skin exposure and inhalation may cause skin rash and damage to the mucous membranes.

COMMENTS: If victims of chemical over-exposure are taken for medical attention, give a copy of the label or this MSDS to the physician/health care professional.

5. FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA: Carbon dioxide, dry chemical or appropriate foam. Water may be effective for cooling containers but not for extinguishing.

EXPLOSION HAZARDS: Closed containers may explode when exposed to fire conditions.

FIRE FIGHTING EQUIPMENT: Self contained breathing apparatus and full protective turn-out gear.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL: Not Available LARGE SPILL: Not Available

ENVIRONMENTAL PRECAUTIONS

WATER SPILL: This material is considered to be a water pollutant and releases of this product should be prevented from contamiating soil and water and from entering drainage and sewer systems. If product is released

Date Issued: 9/30/2009 MSDS No: Q-Plus Date Revised: 10/14/2013

Revision No: 10

Q-Plus Solder Paste Flux

to the environment, take immediate steps to stop and contain release. Caution should be exercised regarding personnel safety and exposure to the related product. Notify local authorities and the National Response Center (NRC), if required.

7. HANDLING AND STORAGE

GENERAL PROCEDURES: No special requirements.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Wear splash goggles or glasses with face shield.

SKIN: Rubber, chemical resistant gloves. When material is heated, wear gloves to protect against thermal burns.

RESPIRATORY: Not normally needed in well ventilated areas. If the ventilation is insufficient to remove smoke from soldering processes, use NIOSH/MSHA approved cartridge type respirator.

PROTECTIVE CLOTHING: Protective clothing and safety shoes as necessary to minimize contact.

WORK HYGIENIC PRACTICES: Good personal hygiene practices should be used. Wash after any contact, before eating, and at the end of the work period.

9. PHYSICAL AND CHEMICAL PROPERTIES

ODOR: Mild.

APPEARANCE: Paste. **COLOR:** Dark amber.

PERCENT VOLATILE: < 1.0 %

FLASH POINT AND METHOD: $> 100^{\circ}\text{C} (212^{\circ}\text{F})$

AUTOIGNITION TEMPERATURE: None

VAPOR PRESSURE: Not Determined VAPOR DENSITY: Not Determined MELTING POINT: 49°C (120°F)

SOLUBILITY IN WATER: Partially Soluble **SPECIFIC GRAVITY:** 1 to 1.033 (water=1)

10. STABILITY AND REACTIVITY

STABLE: Yes

HAZARDOUS POLYMERIZATION: No

STABILITY: Stable under ordinary use and storage conditions.

Date Issued: 9/30/2009 MSDS No: Q-Plus Date Revised: 10/14/2013

Revision No: 10

Q-Plus Solder Paste Flux

POLYMERIZATION: Will not occur. **CONDITIONS TO AVOID:** None

INCOMPATIBLE MATERIALS: Strong oxidizing agents.

11. TOXICOLOGICAL INFORMATION

CARCINOGENICITY

IARC: Not listed.
NTP: Not listed.
OSHA: Not listed.

12. ECOLOGICAL INFORMATION

GENERAL COMMENTS: No information on ecological toxicity or biodegradability is available at this time.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Dispose of this material, contaminated absorbent material and other contaminated materials in an approved waste disposal facility, according to all applicable Federal, State, and Local regulations. Recovery and reuse, rather than disposal, should be the ultimate goal in handling efforts.

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION)

PROPER SHIPPING NAME: Corrosive Solid, N.O.S. (contains Zinc Chloride, anhydrous mixture)

PRIMARY HAZARD CLASS/DIVISION: 8

UN/NA NUMBER: 2331 PACKING GROUP: III

LABEL: Corrosive

15. REGULATORY INFORMATION

UNITED STATES

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

311/312 HAZARD CATEGORIES: Acute health hazard, reactive hazard and fire hazard.

313 REPORTABLE INGREDIENTS: None

TSCA (TOXIC SUBSTANCE CONTROL ACT)

TSCA STATUS: All ingredients are listed or are exempt from listing (as polymers) on the Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

Date Issued: 9/30/2009 MSDS No: Q-Plus Date Revised: 10/14/2013

Revision No: 10

Q-Plus Solder Paste Flux

CALIFORNIA PROPOSITION 65: When used for soldering and similar applications chemicals may be produced which are known to some states to cause birth defects or other reproductive harm.

16. OTHER INFORMATION

REASON FOR ISSUE: New format

APPROVED BY: P. Han **TITLE:** Technical Director

PREPARED BY: J. Saleda-Layton

INFORMATION CONTACT: (630) 628-8083

REVISION SUMMARY: This MSDS replaces the 10/14/2013 MSDS.

HMIS RATING

HEALTH	2
FLAMMABILITY	1
PHYSICAL HAZARD	0
PERSONAL PROTECTION	В

MANUFACTURER DISCLAIMER: The information contained herein is based upon data considered to be accurate and is offered solely for information, customer consideration and investigation. The manufacturer extends no warranties, makes no representations and assumes no responsibility as to the accuracy, completeness or suitability of this data for any purchaser's use. The content of this Material Safety Data Sheet relates only to this product as sold and does not relate to use with any other material or in any process. All chemical products should be used only by, or under, the direction of technically qualified personnel, who are aware of the hazards involved and of the necessity for reasonable care in handling. Hazard communication regulations, United States Occupational Health and Safety (OSHA) and Canadian Workplace Hazardous Materials Information System (WHMIS) require that employees must be trained in the use of Material Safety Data Sheets as a source of hazards information and response.